


Tapered roller bearing 44157X-44348-TIMKEN - 44157X-44348-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/44157x-44348-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽³⁾ C ₂	Factor ⁽⁴⁾ K	Static C ₀	Inner	Outer	
mm	mm	mm	N		N		N			
40.000	88.500	24.765	9900	0.37	2000	2600	0.15	8900	44157X	
1.5748	3.4843	0.9759	23400		5810	7770		19600	44348	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Cr. α ⁽¹⁾	Max Shaft Fillet Radius R ⁽²⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽³⁾	Backing Shoulder Dia. D _s	Cage A ₁ ⁽⁴⁾	A ₂ ⁽⁵⁾	A ₃ ⁽⁶⁾	G ₁	G ₂	C ₃		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
24.765	17.462	3.8	2.3	58.8	58.8	1.5	84.0	75.0	3.3	3.8	22.9	0.7	0.0089	0.88
0.9759	0.6875	0.12	0.09	2.00	2.33	0.06	3.31	2.95	0.13	0.12				1.93

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952312736
Inside diameter	40 mm
Inside diameter	1.575" inch
Outside diameter	88.5 mm
Outside diameter	3.484" inch
Thickness	24.765 mm
Thickness	0.975" inch
Weight	703 g
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE