


## Tapered roller bearing 2984-2925-TIMKEN - 2984-2925-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/2984-2925-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> C <sub>2e</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
46.037	87.312	26.988	3250	0.22	34200	16300	1.68	117000	2984	2925
1.8125	3.4375	1.0625	21000		5400	3220		20000		

Bearing Dimensions										Geometry Factors			Bearing Weight		
Shaft					Housing					Cage		G <sub>1</sub>		G <sub>2</sub>	C <sub>3</sub>
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>f1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	mm	mm		mm		
26.988	22.225	-4.4	3.5	52.8	58.8	2.3	81.8	75.8	1.7	1.1	36.2	15.7	0.0802	6.88	1.90
1.0662	0.8750	-0.25	0.14	2.05	2.31	0.09	3.19	2.95	0.07	0.05					

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952314990
Inside diameter	46.037 mm
Outside diameter	87.312 mm
Thickness	26.988 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE