


Tapered roller bearing 637-632-TIMKEN - 637-632-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/637-632-timken>

TAPERED ROLLER BEARINGS													
SINGLE ROW • TYPE TS													
TYPE TS													
													
Bearing Dimensions				Load Ratings								Part Number	
Bore d	O.D. D	Width B		Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₁₀	Factor ⁽²⁾ e ₁₀	Static C ₂	Inner	Outer			
mm	mm	mm		N		N		N					
60.325	136.525	41.275		22800	0.30	18600	0.30	29800				637	632
2.3750	5.3750	1.6250		52400		13600		67000					
Bearing Dimensions													
Width B	Width C	ER. Dia. a ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backling Shoulder Dia. d _s	Backling Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽¹⁾	Backling Shoulder Dia. D _s	Cage	Geometry Factors			Bearing Weights	
mm	mm	mm	mm	mm	mm	mm	mm	mm	G ₁	G ₂	C ₃	kg	lb
41.275	31.750	-11.2	3.5	72.8	76.8	3.3	125.8	118.8	4.1	2.8	106.4	2.85	6.45
1.6250	1.2500	-0.44	0.14	2.85	3.07	0.13	4.92	4.65	0.16	0.09			

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952318769
Inside diameter	60.325 mm
Outside diameter	136.525 mm
Thickness	41.275 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE