


## Tapered roller bearing 3982X-3927AS-TIMKEN - 3982X-3927AS-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/3982x-3927as-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> C <sub>2e</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
63.500	110.000	29.370	129000	1.45	30000	24800	1.45	191000	2982X	3927AS
2.500	4.331	1.1563	21200		8000	1010		43000		

Bearing Dimensions										Geometry Factors			Bearing Weights	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>				A <sup>(1)</sup>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm					
30.048	23.020	-4.6	7.0	71.0	84.0	0.5	105.0	101.0	2.2	1.2	75.2	21.3	0.1082	1.10
1.1820	0.9063	-0.18	0.28	2.80	3.31	0.02	4.13	3.94	0.08	0.05				2.43

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952319124
Inside diameter	63.5 mm
Inside diameter	2 1/2" inch
Outside diameter	110 mm
Outside diameter	4.331" inch
Thickness	29.37 mm
Thickness	1 5/32" inch
Packaging	1
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE