


Tapered roller bearing 399-393A-TIMKEN - 399-393A-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/399-393a-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ K	Static C ₃	Inner	Outer	
mm	mm	mm	N		N		N			
65.000	112.712	22.225	9500	1.45	22700	16300	12000	300	393A	
2.5591	4.4375	0.8750	28600		5840	3016	28100			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. e ⁽¹⁾	Max Shaft Fillet Radius R ₁ ⁽¹⁾	Backing Shoulder Dia. d ₄ ⁽¹⁾	Max Housing Fillet Radius r ₁ ⁽¹⁾	Backing Shoulder Dia. D ₁ ⁽¹⁾	Cage A ₁ ⁽¹⁾	A ₂ ⁽¹⁾	A ₃ ⁽¹⁾	G ₁	G ₂	C ₁		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
21.986	15.875	-0.8	2.8	71.8	75.8	3.3	195.8	190.0	1.6	2.3	55.0	21.4	0.0964	8.84
0.8690	0.6250	-0.03	0.09	2.80	2.95	0.13	4.13	3.94	0.06	0.09				1.95

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952319636
Inside diameter	65 mm
Inside diameter	2.559" inch
Outside diameter	112.712 mm
Outside diameter	4 7/16" inch
Thickness	22.225 mm
Thickness	7/8" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE