

## Tapered roller bearing 641-632-TIMKEN - 641-632-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/641-632-timken>

TAPERED ROLLER BEARINGS														
SINGLE-ROW • TYPE TS														
TYPE TS														
Bearing Dimensions			Load Ratings						Part Number					
Bore $d$	O.D. $D$	Width $T$	Dynamic <sup>(1)</sup> $C_1$	Factor <sup>(2)</sup> $e$	Dynamic <sup>(1)</sup> $C_{10}$	Factor <sup>(2)</sup> $K$	Static $C_0$	Inner	Outer					
mm	mm	mm	N		N		N							
in	in	in	kN		lbf		klb							
66.675	136.525	41.275	27600	0.30	71000	46000	1.61	298000	541	632				
2.6250	5.3750	1.6250	62100		16100	9900		67000						
Bearing Dimensions														
Bore			Shaft			Housing			Cage		Geometry Factors			
Width $B$	Width $C$	ER. Dr. $\mu m$	Max Shaft Fillet Radius $R_{fs}$	Backing Shoulder Dia. $d_s$	Max Housing Fillet Radius $r_{fs}$	Backing Shoulder Dia. $D_s$	$A_{10}$	$A_{11}$	$G_1$	$G_2$	$C_1$	Bearing Weight		
mm	mm	mm	mm	mm	mm	mm	mm	mm				kg		
in	in	in	in	in	in	in	in	in				lb		
41.275	31.290	-11.2	3.5	77.8	83.8	3.3	125.8	118.8	4.1	3.8	106.4	21.0	0.8614	2.32
1.6250	1.2300	-0.44	0.14	3.03	3.27	0.13	4.92	4.69	0.16	0.09				5.99

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952320168
Inside diameter	66.675 mm
Outside diameter	136.525 mm
Thickness	41.275 mm
Weight	2720 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE