

Tapered roller bearing 6575-6535-TIMKEN - 6575-6535-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/6575-6535-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|----------------------------------------|---------------------------------------|-----------------------|--------|-------------|------|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C _{2e} | Factor ⁽²⁾ C _{2e} | Static C ₂ | Inner | Outer | |
| mm | mm | mm | N | | N | N | N | | | |
| 76.200 | 161.925 | 53.975 | 42900 | 1.52 | 114000 | 26900 | 1.46 | 523000 | 6575 | 6535 |
| 3.0250 | 6.3750 | 2.1265 | 98000 | | 25000 | 13900 | | 118000 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|------------------------------------------|--------------------------------------|--------------------------------------------|--------------------------------------|------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|------|
| Width B | Width C | ER. Dr. a ⁽¹⁾ | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ⁽¹⁾ | Backing Shoulder Dia. D ₁ | Cage A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | A ₃ ⁽¹⁾ | G ₁ | G ₂ | C ₃ | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | kg | |
| 55.150 | 42.862 | -13.2 | 0.4 | 52.6 | 106.6 | 3.3 | 156.8 | 161.8 | 4.1 | 8.9 | 108.6 | 35.5 | 0.1027 | 5.40 |
| 2.1693 | 1.6875 | -0.52 | 0.25 | 3.82 | 4.29 | 0.13 | 6.39 | 5.59 | 0.16 | 0.24 | | | 11.91 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952321745 |
| Inside diameter | 76.2 mm |
| Outside diameter | 161.925 mm |
| Thickness | 53.975 mm |
| Weight | 5400 g |
| Packaging | 1 |
| Standard | No standard |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE