


## Tapered roller bearing 99500-99100-TIMKEN - 99500-99100-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/99500-99100-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
127.000	254.000	66.675	62000	0.41	171900	119000	103000	99500	99100	
5.0000	10.0000	2.6250	148000	1.47	38500	26800	231000			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
66.675	47.625	-12.2	6.4	149.0	158.8	3.3	238.8	227.8	8.7	3.6	55.5	75.5	0.1468	15.48
2.6250	1.8750	-0.48	0.25	5.87	6.25	0.13	9.37	8.94	0.38	0.14			34.07	

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952325170
Inside diameter	127 mm
Outside diameter	254 mm
Thickness	66.675 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE