


# Tapered roller bearing JL730646-L730610-TIMKEN - JL730646-L730610-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/jl730646-l730610-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
150.000	203.200	28.575	19400	1.21	9200	2900	1.27	33000	JL730646	L730610
5.925	8.000	1.126	4300		1130	890		7910		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. r <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>						
28.575	25.406	11.4	3.3	158.0	164.0	3.3	198.0	198.0	2.4	1.5	255.2	103.6	0.1763	2.48
1.126	0.994	0.45	0.13	6.22	6.45	0.13	7.87	7.48	0.09	0.08				5.48

## PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952325910
Inside diameter	150 mm
Outside diameter	203.2 mm
Thickness	28.575 mm
Weight	2480 g
Packaging	1
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE