


Tapered roller bearing 46790A-46720-TIMKEN - 46790A-46720-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/46790a-46720-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ K	Static C ₃	Inner	Outer	
mm	mm	mm	N		N		N			
165.100	225.425	41.275	302000	1.52	18600	11900	429000	46790A	46720	
6.5000	8.8750	1.6250	68200		17700	11900	143000			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Cr. α ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽¹⁾	Backing Shoulder Dia. D _s	A ₁ ⁽¹⁾	A ₂ ⁽¹⁾	Cage	G ₁	G ₂	C ₁		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
38.688	33.338	2.5	0.8	174.0	195.6	3.3	218.0	295.0	3.9	2.8	572.0	174.7	0.1422	4.53
1.5225	1.3125	0.10	0.31	6.85	7.44	0.13	8.58	8.23	0.15	0.09			10.00	

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952326214
Inside diameter	165.1 mm
Inside diameter	6 1/2" inch
Outside diameter	225.425 mm
Outside diameter	8 7/8" inch
Thickness	41.275 mm
Thickness	1 5/8" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE