

Tapered roller bearing 88925-88126-TIMKEN - 88925-88126-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/88925-88126-timken>

| TAPERED ROLLER BEARINGS | | | | | | | | | | | |
|-------------------------|-----------|-----------------|----------------------------------|------------------------------|------------------------------------|-----------------------------------|-----------------|----------|------------------|-------|-----------------|
| SINGLE-ROW • TYPE TS | | | | | | | | | | | |
| TYPE TS | | | | | | | | | | | |
| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C_1 | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C_{10} | Factor ⁽²⁾ e_{10} | Static C_2 | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| in. | in. | in. | kN | | kN | | kN | | | | |
| 234.950 | 320.675 | 50.800 | 92900 | 1.23 | 143000 | 119000 | 821000 | 88925 | 88126 | | |
| 9.2500 | 12.6250 | 2.0000 | 124600 | | 32200 | 26800 | 189000 | | | | |
| Bearing Dimensions | | | | | | | | | | | |
| Shaft | | | Housing | | | | Cage | | Geometry Factors | | Bearing Weights |
| Width B | Width C | ER. Dr. μm | Max Shaft Fillet Radius R_{f1} | Backing Shoulder Dia. d_s | Max Housing Fillet Radius r_{f2} | Backing Shoulder Dia. D_s | A_{10} | A_{11} | G_1 | G_2 | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | kg |
| in. | in. | in. | in. | in. | in. | in. | in. | in. | | | lb. |
| 40.212 | 33.336 | 14.2 | 6.4 | 246.0 | 258.8 | 3.3 | 309.8 | 298.8 | 11.1 | 2.7 | 10.12 |
| 1.5835 | 1.3125 | 0.56 | 0.25 | 9.69 | 10.16 | 0.13 | 12.17 | 11.77 | 0.43 | 0.11 | 22.31 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952327839 |
| Inside diameter | 234.95 mm |
| Outside diameter | 320.675 mm |
| Thickness | 50.8 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE