


Tapered roller bearing EE426200-426330-TIMKEN - EE426200-426330-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/ee426200-426330-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|----------------------------------------|-------------------------|-----------------------|-------------|--------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₀₂ | Factor ⁽²⁾ K | Static C ₀ | Inner | Outer |
| mm | mm | mm | N | | N | | N | | |
| 508.000 | 838.200 | 146.050 | 3070000 | 1.25 | 506000 | 1.22 | 6530000 | EE426200 | 426330 |
| 25.000 | 33.000 | 5.7500 | 812000 | | 218000 | | 1470000 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|-----------------------------------------|---------------------------------------|---------------------------------------------------------|---------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|-------|----------------|--------|
| Shaft | | | | | Housing | | | | | Cage | | | | |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max Shaft Fillet Radius R _{f1} | Backing Shoulder Dia. d _{1s} | Max Housing Fillet Radius r ₁ ⁽²⁾ | Backing Shoulder Dia. D _{1s} | A ₁ ⁽³⁾ | A ₂ ⁽³⁾ | G ₁ | G ₂ | C ₁ | kg | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | |
| 130.700 | 104.775 | 23.9 | 0.7 | 552.0 | 564.6 | 0.7 | 787.7 | 298.0 | 21.5 | 8.3 | 6951.9 | 435.2 | 0.2722 | 290.75 |
| 5.9000 | 4.1250 | 0.94 | 0.38 | 21.75 | 22.25 | 0.38 | 30.22 | 29.88 | 0.94 | 0.93 | | | | 640.99 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952330808 |
| Inside diameter | 508 mm |
| Outside diameter | 838.2 mm |
| Thickness | 146.05 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE