


## Tapered roller bearing 395-3920-B-TIMKEN - 395-3920-B-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/395-3920-b-timken>

**TAPERED ROLLER BEARINGS**  
**TYPE TSF**



Bearing Dimensions				Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factors <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factors <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer		
mm	mm	mm	N		N		N				
63.500	112.712	21.917	9800	0.45	1.45	23000	17000	1.45	12500	305	3620-B
2500	4.4375	0.2117	22300		5700	3570	26100				

Bearing Dimensions						Shaft			Housing		Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a <sup>(3)</sup>	Outer Ring Range D <sub>1</sub> D <sub>2</sub>	Flange Width C <sub>1</sub>	Max Shaft File Radius R <sup>(4)</sup>	Sealing Shoulder Dia. d <sub>1</sub>	Sealing Shoulder Dia. d <sub>2</sub>	Sealing Shoulder Dia. D <sub>1</sub>	D <sub>1</sub>	D <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>		kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	lbs.
21.996	23.812	-4.8	117.370	4.762	3.5	70.6	77.8	108.8	58.0	21.4	0.0984	1.96	4.32	2.32
0.8600	0.9375	-0.03	4.6219	0.1875	0.14	2.78	3.03	4.29						

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952338408
Inside diameter	63.5 mm
Outside diameter	112.712 mm
Thickness	21.996 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE