


Drawn cup roller clutches HFL0822-KF-INA - HFL0822-KF-INA

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup-roller-clutch/hfl0822-kf-ina>

Drawn cup roller clutches HFL0615-KF
with plain or rolling bearing arrangement, plastic springs



F_w	6 mm
D	10 mm
C	15 mm Tolerance: -0.3
F_{ext}	0.3 mm
Drawn cup roller clutches with plain bearing arrangement	
m	4 g Mass
$M_{t, \text{ad}}$	1.76 Nm Permissible torque
n_{Cup}	23000 1/min Limiting speed with rotating shaft (valid for grease and oil lubrication)
n_{Cup}	13000 1/min Limiting speed with rotating outer ring (valid for grease and oil lubrication)
$F_{r, \text{max}}$	110 N Maximum permissible radial load
$n_{\text{Pr}}^{\text{max}}$	18000 N/min Limiting load

Attention!
Drawn cup roller clutches with plain bearings: During operation, the product of the actual speed n and radial load F_r must not exceed the value stated for the limiting load ($F_r \cdot n$) max. The operating limits are determined by the stated limiting speeds and the permissible radial load.

PRODUCT FEATURES

Brand	INA
N° Ean13	3663952345550
Inside diameter	8 mm
Outside diameter	12 mm
Thickness	22 mm
Weight	4 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE