


Self aligning ball bearing 1212-K-TVH-C3-H212-FAG - 1212-K-TVH-C3-H212-FAG

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/sefl-aligning/1212-k-tvh-c3-h212-fag>

Self-aligning ball bearings 1212-K-TVH-C3 + H212
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve



d_{min}	55 mm
D	110 mm
B	22 mm
B_{smin}	5 mm
c	13 mm
D_1	95,8 mm
D_{smax}	101 mm
D_{s1}	80 mm
d	60 mm
d_1	78 mm
d_{smax}	68 mm
d_{s1min}	64 mm
l	39 mm
F_{smax}	1,5 mm
H212	Mass, adapter sleeve
m	0,88 kg Mass
m _s	0,35 kg Mass, adapter sleeve
C _r	30500 N Basic dynamic load rating, radial
e	0,18
Y_1	3,47
Y_2	5,37
C_{10}	11400 N Basic static load rating, radial
Y_0	3,64
n_0	6700 1/min Limiting speed
n_2	8500 1/min Reference speed
C_{10}	710 N Fatigue limit load, radial

PRODUCT FEATURES

Brand	FAG
N° Ean13	3663952346236
Inside diameter	55 mm
Outside diameter	110 mm
Thickness	22 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE