


Self aligning ball bearing 1218-K-TVH-C3-H218-FAG - 1218-K-TVH-C3-H218-FAG

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/sefl-aligning/1218-k-tvh-c3-h218-fag>

Self-aligning ball bearings 1218-K-TVH-C3 + H218
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve



d_{int}	80 mm
D	160 mm
B	30 mm
B_{smin}	6 mm
c	18 mm
D_1	136,7 mm
D_{smax}	149 mm
D_{int}	120 mm
d	90 mm
d_1	112,7 mm
d_{smax}	101 mm
d_{smin}	90 mm
I	82 mm
f_{smax}	2 mm
Accessories	H218 Mass. adapter sleeve
m	2,48 kg Mass
m_1	1,21 kg Mass. adapter sleeve
C	57000 N Basic dynamic load rating, radial
s	0,17
Y_1	3,74
Y_2	5,79
C_{10}	23300 N Basic static load rating, radial
Y_3	3,92
n_{10}	4300 1/min Limiting speed
n_B	6600 1/min Reference speed
C_{10}	1300 N Fatigue limit load, radial

PRODUCT FEATURES

Brand	FAG
N° Ean13	3663952346298
Inside diameter	80 mm
Inside diameter	3.15" inch
Outside diameter	160 mm
Outside diameter	6.299" inch
Thickness	30 mm
Thickness	1.181" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE