


Drawn cup roller bearing YT2520-IKO - YT2520-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/yt2520-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number												
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g			
25	---	---	---	---	---	---	---	---	YT 2520	45			
Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring		
F _w	D	C	t ₂ Max.	Shaft dia. H7 Max.	Shaft dia. H7 Min.	Housing bore dia. N7 Max.	Housing bore dia. N7 Min.	N	N	rpm	IRT 2020-1		
25	33	20	---	25.000	24.987	33.014	32.989	---	---	30 200	55 400	6 000	IRT 2020-1

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952353241
Inside diameter	25 mm
Inside diameter	0.984" inch
Outside diameter	33 mm
Outside diameter	1.299" inch
Thickness	20 mm
Thickness	0.787" inch
Weight	45 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE