

## Tapered roller bearing 32017X-TIMKEN - 32017X-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32017x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(3)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N		N			
85.000	130.000	29.000	19000	0.84	49900	37000	22000	32017X		
3.3465	5.1181	1.1417	43300		11200	8500	52000			

  

Bearing Dimensions										Geometry Factors		Bearing Weight		
Width		ER Dr.		Max Shaft Fillet Radius		Backing Shoulder Dia.		Max Housing Fillet Radius		Backing Shoulder Dia.			Cage	
B	C	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>
29.000	22.000	-0.5	1.5	0.5	0.5	1.5	125.0	118.0	2.5	2.8	100.2	34.9	0.1270	1.30
1.1417	0.8661	-0.02	0.06	0.02	0.02	0.06	4.92	4.69	0.08	0.11				2.63

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	53893778006
Inside diameter	85 mm
Inside diameter	3.346" inch
Outside diameter	130 mm
Outside diameter	5.118" inch
Thickness	29 mm
Thickness	1.142" inch
Weight	1330 g
Packaging	1
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE