

## Tapered roller bearing 30226-TIMKEN - 30226-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30226-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N		N			
in.	in.	in.	lbf		lbf		lbf			
130.000	230.000	43.750	431000	0.84	112000	1.34	950000	30226		
5.1181	9.0551	1.7224	96900		25100		124000			

  

Steering Dimensions										Geometry Factors			Bearing Weight
Drift					Housing					C <sub>1</sub>	C <sub>2</sub>	C <sub>3</sub>	
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Cage A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>					
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	in.	lbs.
40.800	34.000	2.0	4.0	140.0	100.0	3.0	27.0	20.0	2.0	1.1			7.00
1.5748	1.3388	0.08	0.16	5.51	3.94	0.12	1.06	0.79	0.08	0.04			15.50

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354002
Inside diameter	130 mm
Inside diameter	5.118" inch
Outside diameter	230 mm
Outside diameter	9.055" inch
Thickness	43.75 mm
Thickness	1.722" inch
Weight	7060 g
Dynamic load	112 kN
Static load	83.2 kN
Packaging	1
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE