


## Drawn cup roller bearing TAW6212-Z-IKO - TAW6212-Z-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/taw6212-z-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**



TA--Z TLA--Z

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
62	TA	6212 Z	78	---	---	---	---	---	---	---

Boundary dimensions mm	Standard reporting dimensions mm						Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring			
	F <sub>w</sub>	D	C	r <sub>1</sub> Max.	Shaft dia. mm	Housing bore dia. mm							
62	74	12	3.4	62.000	61.981	74.018	73.988	---	---	20 100	30 300	4 500	IRT 5212

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952357447
Inside diameter	62 mm
Inside diameter	2.441" inch
Outside diameter	74 mm
Outside diameter	2.913" inch
Thickness	12 mm
Thickness	0.472" inch
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE