


Drawn cup roller bearing TAW6545-Z-IKO - TAW6545-Z-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/taw6545-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
65	TAW 6545 Z	290	—	—	—	—	—	—	—	—

Boundary dimensions mm		Standard reporting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring		
F _w	D	C	f ₂ Max.	Shaft dia. H7 Max. Min.	Housing bore dia. H7 Max. Min.	N7 Max. Min.	N	N	rpm	IRT 5545			
65	77	45	3.4	65.000	64.981	77.018	76.988	—	—	88 300	207 000	4 000	IRT 5545

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952357508
Inside diameter	65 mm
Inside diameter	2.559" inch
Outside diameter	77 mm
Outside diameter	3.031" inch
Thickness	45 mm
Thickness	1.772" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE