

## Tapered roller bearing 664-654D-TIMKEN - 664-654D-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/664-654d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings								
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup>		Static <sup>(2)</sup>		Dynamic <sup>(3)</sup>		Factor <sup>(4)</sup>		
mm	mm	mm	mm	C <sub>10</sub>	C	N <sub>10</sub>	N	C <sub>10</sub>	C <sub>50</sub>	C <sub>100</sub>	K	
84.138	152.408	95.250	76.200	63000	18700	0.41	1.85	2.48	64000	44800	112000	1.43
3.3125	6.0000	3.7500	3.0000						16400	10100	29100	

  

Part Number		Dimensions				Fit		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	
664	654D	3.5 0.14	198.8 3.94	1.5 0.06	148.8 5.89	-	-	136.6	27.3	0.0819	6.82 15.02

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952358307
Inside diameter	84.138 mm
Inside diameter	3 5/16" inch
Outside diameter	152.4 mm
Outside diameter	6" inch
Thickness	95.25 mm
Thickness	3 3/4" inch
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE