


Drawn cup roller bearing YB66-IKO - YB66-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/yb66-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
9.525 ($\frac{3}{8}$)	—	—	—	—	YB 66	5.3	—	—	—	—	
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	b_2	Shaft dia. h_8	Housing bore dia. J_7	C	C_0	N	N	rpm	
9.525 ($\frac{3}{8}$)	14.288 ($\frac{1}{2}$)	9.52 (3/8)	—	9.525 Max.	9.516 Min.	14.288 Max.	14.280 Min.	6 920	9 410	16 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952361246
Inside diameter	9.525 mm
Outside diameter	14.288 mm
Thickness	9.52 mm
Weight	18 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE