

Drawn cup roller bearing YBH108-IKO - YBH108-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/ybh108-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
15.875 (5/8)	—	—	—	—	—	—	—	—	YBH 108	15.3
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	d_2	Shaft dia. h8	Housing bore dia. J7	C	C_0	rpm		
15.875 / 5/8	22.225 / 7/8	12.70 / 500	—	15.875 Max.	15.864 Min.	22.237 / 22.216	15 000	22 400	9 500	IRB 68-1

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952361659
Inside diameter	15.875 mm
Outside diameter	22.225 mm
Thickness	12.7 mm
Weight	50 g
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE