


## Drawn cup roller bearing BHAM1212-IKO - BHAM1212-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bham1212-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Standard			Closed end			Mass (Ref.) g			Grease retained g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g		
19.050 ( $\frac{3}{4}$ )	—	—	—	—	—	—	—	—	—	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>		Assembled inner ring	
$F_w$	$D$	$C$	Shaft dia. h6		Housing bore dia. J7	C	C <sub>0</sub>	C <sub>0</sub>	rpm				
Max.	Max.	Min.	Max.	Min.	Max.	Min.	N	N					
19.050	26.988	19.051	19.050	19.037	27.000	26.979	16 600	22 600	20 000	IRB 612-1			

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952361819
Inside diameter	19.05 mm
Outside diameter	26.988 mm
Thickness	19.05 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE