


Drawn cup roller bearing BHAM1412-IKO - BHAM1412-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bham1412-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	BHAM 1412	32.5	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. ϕ	Housing bore dia. $J7$	Max.	Min.	C	C_0	rpm	IRB 1012
22.225	30.162	19.05	22.225	22.212	30.176	30.151	18 000	26 100	18 000	IRB 1012

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952361871
Inside diameter	22.225 mm
Inside diameter	7/8" inch
Outside diameter	30.162 mm
Outside diameter	1 3/16" inch
Thickness	19.05 mm
Thickness	3/4" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE