


Drawn cup roller bearing BAM228-IKO - BAM228-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam228-iko>



IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Standard			Closed end			Mass (Ref.) g			Grease retained g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g				
34.925 (1 3/8)	---	---	---	---	---	---	---	---	BAM 228	29	---	---

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynam. load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring	
F _w	D	C ₀	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	C ₀	N	N	rpm
34.925	41.275	12.70	34.925	34.909	41.289	41.264	9 770	16 600	10 000	IRB 188	

Notes*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952363035
Inside diameter	34.925 mm
Outside diameter	41.275 mm
Thickness	12.7 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE