


Drawn cup roller bearing YB2610-IKO - YB2610-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/yb2610-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number											
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g			
41.275 (1 5/8)	—	—	—	—	—	—	—	—	YB 2610 — 69			
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm	Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C_1	t_1	Shaft dia. mm	Housing bore dia. mm	C	C_0	N	N	rpm	IRB 2210	
41.275 (1 5/8)	50.800 2	15.88 (625)	—	41.275 Max. 41.259 Min.	50.818 Max. 50.788 Min.	37 000	71 700	3 500	—	—	—	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952363219
Inside diameter	41.275 mm
Outside diameter	50.8 mm
Thickness	15.88 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE