


Needle roller bearing GBRI162816-IKO - GBRI162816-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/gbri162816-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
25.400 (1)	GBRI 162816	184	25.400 (1)	44.450 (1) (2)	25.400 (1)	25.650	31.750 (1) (2)
Standard mounting dimensions mm		Ball diam. mm C	Basic load rating N	Dynamic load rating C _g N	Allowable rotational speed (°) rpm	Assembled inner ring	
d _s Min. Max.	D _s Max.					r _{as} max (°)	LRBZ 162016
30.5	30.7	39.6	0.6	46 600	83 900	4 500	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377445
Inside diameter	25.4 mm
Outside diameter	44.45 mm
Thickness	25.65 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE