

Needle roller bearing RNA6903-U-IKO - RNA6903-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/rna6903-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_f (1)
22	—	—	—	RNA 6903U	40.5	22	30	23	0.3

Standard rounding dimension D_s Max. mm	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)
28	19 800	30 600	8 500

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952378923
Inside diameter	22 mm
Inside diameter	0.866" inch
Outside diameter	30 mm
Outside diameter	1.181" inch
Thickness	23 mm
Thickness	0.906" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE