


Needle roller bearing RNA4919-U-IKO - RNA4919-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/rna4919-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|---|--|---|---|---------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_a (1) |
| 110 | — | RNA 4919U | — | — | 760 | 110 | 130 | 35 | 1.1 |
| Standard rounding dimension D_s Max. mm | | | | | | | | | |
| | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed (reference) rpm | | | | | | |
| 123.5 | 109 000 | 250 000 | 1 700 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952379814 |
| Inside diameter | 110 mm |
| Outside diameter | 130 mm |
| Thickness | 35 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE