


Needle roller bearing RNA4924-UU-IKO - RNA4924-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/rna4924-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm		
	With two seals	With one seal	With two seals	With one seal		F_w	D	C (1)
135	RNA 4924UU	—	—	—	1 940	135	165	45 1.1
Standard mounting diameter D_A Max. mm	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed (1) rpm					
158.5	178 000	410 000	1 400					

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379906
Inside diameter	135 mm
Outside diameter	165 mm
Thickness	45 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE