

Needle roller bearing NA4900-U-IKO - NA4900-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na4900-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|------------------|-----------------------|-----------------|----------------|---------------|---------------------|---------------------------|----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B |
| 10 | — | NA 4900U | — | — | 24.5 | 10 | 22 | 13 | 14 |

| r _s mm ⁽¹⁾ | F _w | Standard mounting dimensions mm | | | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | |
|----------------------------------|----------------|------------------------------------|------|------|---|--|----------------------|-------------|
| | | Min. | Max. | Max. | | | | |
| 0.3 | 14 | 12 | 13 | 20 | 8 080 | 8 490 | 14 000 | LRTZ 101414 |

Note(1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952381060 |
| Inside diameter | 10 mm |
| Outside diameter | 22 mm |
| Thickness | 14 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE