

Needle roller bearing NA6901-U-IKO - NA6901-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na6901-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
12	—	—	—	—	NA 6901U	45.5	12	24	22	23

r_s min (1)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Basic dynamic load rating C_1 N	Allowable rotational speed(2) rpm	Assembled inner ring LRTZ 121623
		Min.	Max.	d_s				
0.3	16	14	15	22	15 500	20 400	12 000	

Note(1) Minimum allowable value of diameter dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381107
Inside diameter	12 mm
Outside diameter	24 mm
Thickness	23 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE