

Needle roller bearing NA6903-U-IKO - NA6903-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na6903-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
17	—	—	—	—	NA 6903U	68.5	17	30	23	24

r_s min (1)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Allowable rotational speed(2) rpm	Assembled inner ring
		Min.	Max.	D_s Max.			
0.3	22	19	21	28	19 800	30 600	8 500

Note(1) Minimum allowable value of diameter dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381206
Inside diameter	17 mm
Outside diameter	30 mm
Thickness	24 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE