

## Needle roller bearing NA4904-U-IKO - NA4904-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na4904-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
<b>20</b>	—	<b>NA 4904U</b>	—	—	78.5	20	37	17	18

r <sub>s</sub> min ( <sup>1)</sup> )	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.				
0.3	25	22	24	35	18 000	20 500	7 500	LRTZ 202518

Note<sup>(1)</sup> Minimum allowable value of diameter dimension r  
 Note<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381213
Inside diameter	20 mm
Outside diameter	37 mm
Thickness	18 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE