

Needle roller bearing NA6905-U-IKO - NA6905-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na6905-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|------------------|-----------------------|---------------|----------------|---------------|---------------------|---------------------------|----|----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B | |
| 25 | — | — | — | — | NA 6905U | 162 | 25 | 42 | 30 | 31 |

| r _s min (1) | F _w | Standard mounting dimensions mm | | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring |
|---------------------------|----------------|------------------------------------|---------------------|---|--|----------------------|
| | | d _s Min. | d _s Max. | | | |
| 0.3 | 30 | 27 | 29 | 39 200 | 58 700 | LRTZ 253031 |

Note(1) Minimum allowable value of diameter dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952381312 |
| Inside diameter | 25 mm |
| Outside diameter | 42 mm |
| Thickness | 31 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE