

## Needle roller bearing NA49-32-U-IKO - NA49-32-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na49-32-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
32	—	NA 49/32U	—	—	167	32	52	20	21

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRTZ 324021
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.			
0.6	40	36	39	48	29 400	44 200	5 000

Notes: (1) Minimum allowable value of diameter dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381428
Inside diameter	32 mm
Outside diameter	52 mm
Thickness	21 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE