

## Needle roller bearing NA4907-U-IKO - NA4907-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na4907-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
35	—	NA 4907U	—	—	179	35	55	20	21

r <sub>s</sub> min ( <sup>1</sup> )	F <sub>w</sub>	Standard mounting dimensions mm				Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		Min.	Max.	d <sub>s</sub>	D <sub>s</sub> Max.			
0.6	42	39	41	51	30 100	46 300	4 500	LRTZ 354221

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381466
Inside diameter	35 mm
Outside diameter	55 mm
Thickness	21 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE