

## Needle roller bearing NA6915-UU-IKO - NA6915-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na6915-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
75	—	—	NA 6915UU	—	1 480	75	105	54	55

r <sub>s</sub> mm	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
		Min.	Max.	D <sub>s</sub> Max.				
1	85	80	83	100	128 000	299 000	2 000	LRTZ 758555

Note(1) Minimum allowable value of shaft dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381800
Inside diameter	75 mm
Outside diameter	105 mm
Thickness	55 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE