

Needle roller bearing NA4918-UU-IKO - NA4918-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na4918-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|------------------|-----------------------|---------------|----------------|---------------------|---------------------------|----|-----|----|----|
| | With two seals | With one seal | With two seals | | With one seal | d | D | C | B |
| 90 | NA 4918UU | — | — | — | 1 360 | 90 | 125 | 35 | 36 |

| r_s mm | F_w | Standard mounting dimensions mm | | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | |
|----------|-------|------------------------------------|------|--|--|----------------------|-------|--------------|
| | | Min. | Max. | | | | | |
| 1.1 | 105 | 96.5 | 103 | 118.5 | 106 000 | 238 000 | 1 800 | LRTZ 9010536 |

Note⁽¹⁾ Minimum allowable value of outer diameter r
 Note⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark: The outer ring has an oil groove and an oil hole.
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952381893 |
| Inside diameter | 90 mm |
| Outside diameter | 125 mm |
| Thickness | 36 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE