

## Needle roller bearing NA4919-UU-IKO - NA4919-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na4919-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
95	NA 4919UU	—	—	—	1 420	95	130	35	36

r <sub>s</sub> mm	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub>	Basic dynamic load rating C <sub>10</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring	
		d <sub>s</sub> Min.	d <sub>s</sub> Max.					D <sub>s</sub> Max.
1.1	110	101.5	108	123.5	109 000	250 000	1 700	LRTZ 9511036

Notes: (1) Minimum allowable value of diameter dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381930
Inside diameter	95 mm
Outside diameter	130 mm
Thickness	36 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE