

Needle roller bearing NA6919-U-IKO - NA6919-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na6919-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
95	—	—	—	NA 6919U	2 600	95	130	63	64

r _s mm	Standard mounting dimensions	Basic dynamic load rating		Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
		d _s Min.	d _s Max.			
1.1	110 101.5 108	123.5	177 000	493 000	1 700	LRTZ 9511064

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: (1) The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381954
Inside diameter	95 mm
Outside diameter	130 mm
Thickness	64 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE