

Needle roller bearing NA4922-U-IKO - NA4922-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na4922-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
110	—	NA 4922U	—	—	2 150	110	150	40	41

r _s mm	F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min.	Max.	Max.				
1.1	125	116.5	123	143.5	140 000	322 000	1 500	LRTZ 11012541

Notes: (1) Minimum allowable value of diameter dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381992
Inside diameter	110 mm
Outside diameter	150 mm
Thickness	41 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE