

Needle roller bearing NA4926-UU-IKO - NA4926-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na4926-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
130	NA 4926UU	—	—	—	4 080	130	180	50	51

r _s min (°)	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		d _s Min.	d _s Max.				
1.5	150	138	148	206 000	511 000	1 300	LRTZ 13015051

Note(1) Minimum allowable value of outer diameter r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382043
Inside diameter	130 mm
Outside diameter	180 mm
Thickness	51 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE