

## Needle roller bearing NA4928-UU-IKO - NA4928-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/na4928-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
140	NA 4928UU	—	—	—	4 340	140	190	50	51

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub>	Basic dynamic load rating C <sub>10</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		d <sub>s</sub> Min.	d <sub>s</sub> Max.					D <sub>s</sub> Min.
1.5	160	148	158	182	214 000	549 000	1 200	LRTZ 14016051

Note(1) Minimum allowable value of shaft dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382050
Inside diameter	140 mm
Outside diameter	190 mm
Thickness	51 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE