


## Needle roller bearing BR122016-U-IKO - BR122016-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/br122016-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>19.050</b> ( $\frac{3}{4}$ )	<b>BR 122016 U</b>		68	19.050 ( $\frac{3}{4}$ )	31.750 (1 $\frac{1}{4}$ )	25.400 (1 )
Standard mounting dimensions mm		Basic dynamic load rating $C$	Static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_1$	$r_{as}$ max	N	N	rpm		
26.5	1.0	20 700	24 400	10 000		

Note<sup>(1)</sup> Minimum allowable value of chamfer dimension  $r$   
<sup>(\*)</sup> Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382104
Inside diameter	19.05 mm
Outside diameter	31.75 mm
Thickness	25.4 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE