


## Needle roller bearing BRI142620-UU-IKO - BRI142620-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bri142620-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>22.225</b> ( $\frac{7}{8}$ )	<b>BRI 142620 UU</b>		177	22.225 ( $1 \frac{1}{4}$ )	41.275 ( $1 \frac{3}{4}$ )	31.750 ( $1 \frac{1}{4}$ )	32.000	

$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring LRBZ 141820 B
	Min.	Max.	Max. as max. <sup>(*)</sup>				
28.575 ( $1 \frac{1}{4}$ )	27	27.5	36.0	34 900	49 900	7 000	

Notes: (\*) Minimum allowable value of diameter dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382548
Inside diameter	22.225 mm
Outside diameter	41.275 mm
Thickness	31.75 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE