

Needle roller bearing BRI162820-U-IKO - BRI162820-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bri162820-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
25.400 (1)		BRI 162820 U	196	25.400 (1)	44.450 (1 $\frac{1}{4}$)	31.750 (1 $\frac{1}{4}$)	32.000	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
	Min.	Max.	Max. as max. ⁽¹⁾					
31.750 (1 $\frac{1}{4}$)	30.5	30.7	39.2	36 000	53 500	6 500	LRBZ 162020 B	

Notes: (1) Minimum allowable value of diameter dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382562
Inside diameter	25.4 mm
Outside diameter	44.45 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE