

Needle roller bearing BRI203320-UU-IKO - BRI203320-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bri203320-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
31.750 (1 1/4)	BRI 203320 UU		254	31.750 (1 1/4)	52.388 (2 1/8)	31.750 (1 1/4)	32.000
F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 202420 B
	Min.	Max.	Misg. as max. ⁽¹⁾				
38.100 (1 1/2)	37	37.1	45.1	43 700	66 900	5 500	

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382616
Inside diameter	31.75 mm
Outside diameter	52.388 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE